



Item# \_\_\_\_\_

Job \_\_\_\_\_



### Standard



5MB Wheel Brake



5M Resilient

### Stainless Steel, Cart Washable



5MDBGSA



5MDGSA

### Polymer Casters



5PC



5PCB

## METRO™ STEM CASTERS

- **Metro Stem-Type Casters** are designed to fit Super Erecta Shelf® posts to form shelf carts and other mobile units.
- **Stainless Steel, Cart-Washable Casters** offer grease seals and zerk fittings. Can withstand high-pressure washings.
- **Polymer Casters:** Innovative polymer stem casters offer total corrosion resistance and enhanced durability. For all medium-duty applications.
- **Resilient Rubber Tread:** A molded, soft tread that provides good floor protection along with quiet operation. Non-marking.
- **Polyurethane Tread:** Long-wearing; resists abrasion. Non-marking, shock absorbing.
- **Wheel Brakes:** Foot-operated. Available on all caster models.
- **Caster Load Ratings:** From 125 lbs. to 300 lbs. (57 to 136kg).
- **Donut Bumpers:** Furnished standard on all Metro stem casters.
- **Additional Caster Types Available.**

**Note:** SPECIAL WHEELS — V-groove, Conductive, Steel and Phenolic — are available on request. For additional information, contact InterMetro Industries Corporation or your InterMetro representative.





# METRO™ STEM CASTERS

## DIMENSIONS: Standard Casters — Stem-Type

Cat. No.	Type	Wheel Dia.		Face		Wheel Tread	Load Rating		Approx. Pkd. Wt.	
		(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)	(lbs.)	(kg)
4LD	Stem/Swivel	4	102	1/2	12	Resilient	125	56	1 1/2	.6
5LD	Stem/Swivel	5	127	1/2	12	Resilient	125	56	2	.9
5M	Stem/Swivel	5	127	1 1/4	32	Resilient	200	90	2 1/2	1.1
5MB	Stem/Brake	5	127	1 1/4	32	Resilient	200	90	2 3/4	1.2
5MR	Stem/Rigid	5	127	1 1/4	32	Resilient	200	90	3 1/2	1.5
5MDA	Stem/Swivel	5	127	1 1/4	32	High Modulus Donut	250	111	2 1/2	1.1
5MDBA	Stem/Brake	5	127	1 1/4	32	High Modulus Donut	250	111	2 5/8	1.17
5MDRA	Stem/Rigid	5	127	1 1/4	32	High Modulus Donut	250	111	2 5/8	1.08
5MP	Stem/Swivel	5	127	1 1/4	32	Polyurethane	300	135	2 1/8	.94
5MPB	Stem/Brake	5	127	1 1/4	32	Polyurethane	300	135	2 1/4	1
5MPR	Stem/Rigid	5	127	1 1/4	32	Polyurethane	300	135	2	.9

**NOTE 1:** Stem casters are shipped with donut bumper **at no additional charge.**

**NOTE 2:** Rigid casters are held in position by a connecting channel. When ordering rigid casters, shelf width must be known.

**NOTE 3:** Load Height for all 5M, 5MD and 5MP casters — 6 7/32" ± 1/16" (155 ± 1.5mm).

**NOTE 4:** Load Height for 4LD caster — 4 5/8" ± 1/16" (118 ± 1.5mm).

**NOTE 5:** Load Height for 5LD caster — 5 5/8" ± 1/16" (143 ± 1.5mm).

**NOTE 6:** Brakes are foot-operated.

## DIMENSIONS: Stainless Steel Cart-Washable Casters — Stem-Type

Cat. No.	Type	Wheel Dia.		Face		Wheel Tread	Load Rating		Approx. Pkd. Wt.	
		(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)	(lbs.)	(kg)
5MDGSA	Swivel	5	127	1 1/4	32	High Modulus Donut	150	68	2 1/2	1.1
5MDBGSA	Brake	5	127	1 1/4	32	High Modulus Donut	150	68	2 5/8	1.17
5MDRGSA	Rigid	5	127	1 1/4	32	High Modulus Donut	150	68	2 5/8	1.08
5MPGSA	Swivel	5	127	1 1/4	32	Polyurethane	300	135	2 1/8	.94
5MPBGSA	Brake	5	127	1 1/4	32	Polyurethane	300	135	2 1/4	1
5MPRGSA	Rigid	5	127	1 1/4	32	Polyurethane	300	135	2	.9

**NOTE 1:** Stem casters are shipped with donut bumper **at no extra charge.**

**NOTE 2:** Rigid casters are held in position by a connecting channel. When ordering rigid casters, shelf width must be known.

**NOTE 3:** Load Height for all 5MD and 5MP casters — 6 7/32" ± 1/16" (155 ± 1.5mm).

**NOTE 4:** All casters are grease sealed with zerk fittings in swivel and axle.

**NOTE 5:** Brakes are foot-operated.

**NOTE 6:** "D" in model number designates donut wheel made of high-modulus rubber.

## DIMENSIONS: Polymer Casters — Stem-Type

Cat. No.	Type	Wheel Dia.		Face		Wheel Tread	Load Rating		Approx. Pkd. Wt.	
		(in.)	(mm)	(in.)	(mm)		(lbs.)	(kg)	(lbs.)	(kg)
5PC	Swivel	5	127	1 1/4	32	Polyurethane	300	135	2	.9
5PCB	Brake	5	127	1 1/4	32	Polyurethane	300	135	2	.9
5PCR	Rigid	5	127	1 1/4	32	Polyurethane	300	135	2	.9

**NOTE 1:** Optional thread guards (blue) may be ordered by adding "-TG" to the desired model number (eg. 5PC-TG, 5PCB-TG, 5PCR-TG)

**NOTE 2:** Stem casters are shipped with donut bumpers **at no extra charge.**

**NOTE 3:** Rigid casters are held in place by a connecting channel. When ordering, shelf depth **must be** provided.

**Manufactured by:**  
**InterMetro Industries Corp.**  
North Washington Street  
Wilkes-Barre, PA 18705

Phone 717-825-2741  
FAX 717-825-2852  
For Product Information, call 1-800-433-2232  
For Customer Service, call 1-800-992-1776



**InterMetro Industries Corporation**  
North Washington Street  
Wilkes-Barre, PA 18705  
www.metro.com

L02-041  
Rev. 9/98 BJ  
Printed in U.S.A.  
Information and specifications are subject to change  
without notice. Please confirm at time of order.